PRODUCT INFORMATION Formaldehyde Solidifier FSC-1

Fast absorption of formaldehyde spills

Summary

- + Easy to applicate: Open shaker, push paper protection, and generously sprinkle onto the spillage. Leave it to solidify for a short time, then absorb quickly with scoop and plastic scraper and close airtight in a waste bag/ waste container with the cable tie. Thereafter, dispose according to the waste key 07 01 04*.
- + Application area: Formaldehyde spills, 4% (e.g. pathology)
- + **Binding characteristics:** For Formaldehyde No guarantee for other chemicals!

+ Wear protective clothing when removing spills: Wear tested PPE (gown, protective gloves, protective boots) of the highest category III with proved protection against Formaldehyde. Pay attention to the corresponding permeation times ! In addition, you should wear a gas filtering respirator (half-mask or full face mask, no FFP masks) with appropriate filters and gas-tight goggles.

+Disposal: Waste in need of supervision or need of special supervision (waste bag: 07 01 04*); separately collect and dispose airtight!

Version

100112
100113
ristics
1 g FSC-1 = Ø 245 g Formaldehyde 4%
312 g solidifier
In closed container, dark and dry
Producer: Safetec of America Inc., USA. Distributor: Berner International GmbH, Werner-von-Siemens-Str. 19, 25337 Elmshorn, Germany Tel: +49 4121 4356 - 0, Fax: +49 4121 4356 - 20, info@berner-safety.de, www.berner-safety.de
-

Berner International GmbH Contact Werner-von-Siemens-Str. 19 Tel +49 4121 4356-0 D-25337 Elmshorn

Fax +49 4121 4356-20

GB-12 1231 B.doc Prepared: T. Mürdel - Approved: I. Britton Valid from: 27 May 2016

